



02

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04Q 7/22, H04L 12/56</b>	<b>A1</b>	(11) International Publication Number: <b>WO 97/21313</b> (43) International Publication Date: <b>12 June 1997 (12.06.97)</b>
(21) International Application Number: <b>PCT/GB96/02962</b> (22) International Filing Date: <b>29 November 1996 (29.11.96)</b>  (30) Priority Data: 9524585.8      1 December 1995 (01.12.95)      GB 9524649.2      1 December 1995 (01.12.95)      GB  (71) Applicant (for all designated States except US): <b>NORTHERN TELECOM LIMITED [CA/CA];</b> World Trade Center of Montreal, 8th floor, 380 St Antoine Street West, Montreal, Quebec H2Y 3Y4 (CA).  (72) Inventors; and (75) Inventors/Applicants (for US only): <b>RICHARDSON, Kenneth [GB/GB];</b> Nortel Technology Limited, BNR Park, Norreys Drive, Maidenhead, Berkshire SL6 4AG (GB). <b>SAYERS, Ian [GB/GB];</b> Nortel Technology Limited, BNR Park, Norreys Drive, Maidenhead, Berkshire SL6 4AG (GB).  (74) Agent: <b>RYAN, John, Peter, William; Nortel Limited, Patents and Licensing, West Road, Harlow, Essex CM20 2SH (GB).</b>		(81) Designated States: <b>U.S. European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b>  Published <i>With international search report.</i>
(54) Title: <b>MOBILE PACKET DATA COMMUNICATIONS SYSTEM</b>  <div data-bbox="370 1150 1218 1774" data-label="Diagram"> </div> (57) Abstract <p>Packet data is routed from a packet data network (18) to a mobile subscriber (10) served by a base station (12) and a base station controller (13) by encapsulating the packet and providing the encapsulated packet with temporary address information for transport of the packet to the mobile subscriber (10) via the base station controller (13).</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## MOBILE PACKET DATA COMMUNICATIONS SYSTEM

This invention relates to mobile communications systems and in particular to the provision of packet data services in a mobile system.

### BACKGROUND OF THE INVENTION

- 5 Mobile telephone networks were originally developed to provide voice services to customers. However, customers are now demanding access to many of the services, including packet data services, that are provided on the conventional wired network. A general description of a packet data network is given in specification  
10 No. WO 95/16330 and in specification No. EP-A2-0,642,283.

- It is of course difficult to determine the precise location of a mobile user who is free to roam throughout the mobile service area. There is thus a problem of routing traffic from a fixed packet data network to  
15 the mobile subscriber. In the normal circuit switched network this problem is addressed by using the call forward facility to direct a mobile terminated call to the mobile switching centre (MSC) serving the subscriber. In a fixed packet data network however, this call forwarding facility is not provided and thus the support of dynamic  
20 routing to mobile customers can be difficult and costly. This is a particular problem as, unlike a circuit switched call where a connection is established for the duration of the call, each packet must be delivered separately to the correct mobile terminal.

### 25 SUMMARY OF THE INVENTION

The object of the invention is to minimise or to overcome this disadvantage.

It is a further object of the invention to provide an improved method and apparatus for routing packet data to terminals in a mobile communications network.

- 5 According to one aspect of the invention there is provided a method of routing packet data from a packet data network to a mobile network subscriber terminal served by a base station controller and a mobile switching centre for provision of voice facilities to the terminal and by a mobile packet switch for delivery of packet data to the
- 10 terminal, each said mobile terminal adapted to receive packet data services having a respective public network data number allocated thereto, the method including encapsulating each data packet, providing from the mobile network to the data packet information indicative of the mobile network location of each said mobile terminal
- 15 adapted to receive packet data services, providing each said encapsulated data packet with a temporary address corresponding to said mobile network location whereby that packet is routed via the packet switch to the base station controller serving that mobile terminal, decapsulating the data packet, and delivering the packet to
- 20 the mobile terminal.

- According to another aspect of the invention there is provided a mobile communications network having means for delivery of packet data services from a packet data network to mobile terminals served
- 25 by the mobile network, the mobile network including a mobile switching centre for providing voice communication facilities to mobile terminals via respective base station controllers and base stations, a home location register for storing information relating to said mobile terminals, and packet switching means providing an
- 30 interface between the packet data network and said mobile terminals via the respective base station controllers, the network including means for encapsulating each data packet, means for retrieving from the mobile network to the data packet network said stored information indicative of the mobile network location of each said
- 35 mobile terminal adapted to receive packet data services, means for providing each said encapsulated data packet with a temporary

address corresponding to said mobile network location whereby that packet is routed via the packet switch to the base station controller serving that mobile terminal, and means for decapsulating the data packet, and delivering the packet to the mobile terminal.

5

According to a further aspect of the invention there is provided a mobile communications network having means for delivery of packet data services from a packet data network to mobile terminals served by the mobile network, the mobile network including a mobile  
10 switching centre for providing voice communication facilities to mobile terminals via respective base station controllers and base stations, a home location register for storing information relating to said mobile terminals, a packet routing system comprising a gateway support node providing an interface with the packet data network and  
15 one or more serving support nodes each coupled to the gateway support node and to one or more base station controllers for delivery of data packets to the mobile terminals, the packet routing system including means for encapsulating each data packet, means for retrieving from the mobile network to the data packet network said  
20 stored information indicative of the mobile network location of each said mobile terminal adapted to receive packet data services, means for providing each said encapsulated data packet with a temporary address corresponding to said mobile network location whereby that packet is routed via the packet switch to the base station controller  
25 serving that mobile terminal, and means for decapsulating the data packet, and delivering the packet to the mobile terminal.

The mobile terminal address may be a data network number or a roaming data number.

30

### **DESCRIPTION OF PREFERRED EMBODIMENTS**

Embodiments of the invention will now be described with reference to the accompanying drawings in which:

35 Figure 1 is a schematic diagram of a mobile telecommunications network supporting both voice and packet data services;

Figure 2 illustrates the network of figure 1 in further detail showing the signalling and data transfer interfaces;

- 5     Figures 3a and 3b are flowcharts illustrating the state models of a mobile terminal and a packet data server in the network of figures 1 and 2;

- 10     Figure 4 is a chart illustrating a combined IMSI/packet service attach procedure for a mobile terminal in the network of figures 1 and 2; and

- 15     Figures 5 and 6 illustrate encapsulated data packet formats for data transport respectively between support nodes and between a server support node and a mobile terminal in the network of figures 1 and 2;

- Referring to figures 1 and 2, the mobile system, which may for example conform to the European GSM or to the North American  
20     PCS 900, standard, includes an array of cells 11 each served by a respective base station (BTS) 12 providing communication with subscriber terminals 10 currently located in that cell. A number of base stations are controlled by a base station controller (BSC) 13 which in turn is coupled to a mobile switching centre (MSC) 14. The  
25     mobile switching centre incorporates a database or visitors location register (VLR) 15 containing information on the cellular location of mobile terminals 10 currently in the service area of that mobile switching centre. Movement of a mobile terminal from one system cell to another results in corresponding updating of the information  
30     relating to that terminal stored in the VLR. Information on all system mobiles 10 is stored in a central database or home location register (HLR) 16 which may be accessed by the mobile switching centre to update the VLR whenever a mobile terminal enters the service area of the mobile switching centre. Verification of a mobile terminal's right  
35     to access the system may be performed by comparison of that terminal's international mobile subscriber identity (IMSI) with

corresponding information stored in an equipment identity register (EIR) associated with or forming part of the VLR.

The mobile switching centre provides a coupling between the mobile system and fixed networks, e.g. a PSTN 17 for voice and circuit data services to the mobile terminals. Packet data services are provided to the mobile terminals from a fixed packet data network 18 via a gateway general packet radio service support node (GGSN) 19 and a serving support node (SGSN) 20 which provide a packet switching function to control routing of data packets to respective mobile terminals within the mobile network. In this arrangement, the GGSN and SGSN are considered as forming part of the mobile network and thus provide an interface between the mobile network and the data network. Signalling interfaces are provided between the home location register and the GGSN and SGSN, and between the mobile switching centre and the BSC and SGSN. As shown in figure 1, information relating to packet data services may be stored in a general packet radio service register (GR) 21 associated with the home location register rather than in the home location register itself.

Information relating to mobile terminals is provided to the gateway support node 20 from the home location register 16 or from the general packet radio service register 21 to facilitate routing of data packets to mobile terminals via an appropriate serving support node 20. This information is stored in the gateway support node 20 and is updated directly or indirectly by the home location register only when necessary, e.g. when a mobile terminal moves from the service area of one mobile switching centre to another.

Referring now to figures 3a and 3b, these illustrate the packet data service attachment and detachment procedures for a mobile terminal and a serving support node respectively. In each case, the movement from one state to the next is dependent on the current state and the event that has occurred. The general combined IMSI/packet services attach procedure for a mobile terminal is illustrated in figure 4

In the mobile network, each subscriber terminal 10 is allocated a public data network number which is used within the mobile network as a roaming number by the mobile terminal for packet data purposes. This number is allocated when the mobile terminal initiates the attach function and corresponds to a temporary logical link identity for the delivery of data services to the terminal. In one embodiment of our arrangement, the home location register 16 includes a facility for translating this data network number into the subscriber's international mobile station identity (IMSI) and for providing this information to the gateway support node 19. This provides a common initial point of contact with the packet data network and the administration of network resources is simplified by concentrating the information into a single entity.

15 Within the network of figures 1 and 2, data packets are encapsulated and subsequently decapsulated for routing purposes between the packet data network and the mobile terminal. Two forms of encapsulation are employed, one for routing the packet between the GGSN and SGSN and the second for routing from the SGSN to the mobile terminal. Each packet is decapsulated prior to delivery to the mobile terminal. As shown in figure 4, each data packet incorporates a payload and a header including a support node (GSN) address and a message end point identifier (DEST) determined from that terminal's public data number together with location information provided from the HLR or, where the packet data is to be multicast to a group of subscribers, the IMGI (international mobile group identity) of that subscriber group. The header may also contain information identifying the type of message, i.e. indicative of whether the message is point-to-point, multicast or broadcast. For routing from the SGSN to the mobile, the data packet is encapsulated, as shown in figure 5, with a header incorporating the logical link identifier and, where more than one data protocol is employed, a service access point identifier. Each packet is thus routed via the GGSN and SGSN to the base station controller serving the mobile terminal.



Decapsulation of the packet is performed, e.g. by the base station controller prior to delivery of the packet to the mobile terminal.

- 5 The requirements for identifiers are detailed in Table 1 below which relates to service provider messages and in Table 2 below which relates to service subscriber messages:-

Table 1

## Service Provider Message Header

	Singlecast Ack	Singlecast Unack.	Multicast	Broadcast	Acknowledge
Provider Identifier	M	M	M	M	M
Message Type Identifier	M	M	M	M	M
Subscriber Identifier	M	M	NA	NA	M
User Identifier	O	O	M	M	NA
Group Identifier	NA	NA	M	NA	NA

Table 2

## Service Subscriber Message Header

	Registration	Deregistration	Singlecast Ack.	Singlecast Unack.	Acknowledge
Provider Identifier	M	M	M	M	M
Message Type Identifier	M	M	M	M	M
Subscriber Identifier	M	M	M	M	M
Area Identifier	NA	NA	NA	NA	NA
Group Identifier	NA	NA	NA	NA	NA

In Tables 1 and 2, the reference M signifies that the identifier is mandatory, O that an identifier is optional, and NA that an identifier is not Applicable

- 5 In a second embodiment, a roaming data call number is employed for each subscriber terminal. In this arrangement, the user's data call number is forwarded by the GGSN to the home location register 16. To ensure routing of the data packet to the correct SGSN for delivery to the mobile terminal 10, the HLR changes the current address
- 10 associated with the packet into a roaming data number that is then used to address the SGSN currently serving the mobile terminal. This number is fixed in the network and routes the packet to the serving SGSN which is then responsible for forwarding the packet on the radio link with the mobile terminal's correct address. The mobile
- 15 terminal 10 which is listening to the radio link can then recognise its own address and extract the data packet. Any response by the mobile can use its own address. Alternatively, a semi-permanent association may be made for the duration of the data transfer

10.

**CLAIMS:**


1. A method of routing packet data from a packet data network to a mobile network subscriber terminal served by a base station controller and a mobile switching centre for provision of voice facilities to the terminal and by a mobile packet switch for delivery of packet data to the terminal, each said mobile terminal adapted to receive packet data services having a respective public network data number allocated thereto, the method including encapsulating each data packet, providing from the mobile network to the data packet information indicative of the mobile network location of each said mobile terminal adapted to receive packet data services, providing each said encapsulated data packet with a temporary address corresponding to said mobile network location whereby that packet is routed via the packet switch to the base station controller serving that mobile terminal, decapsulating the data packet, and delivering the packet to the mobile terminal.
2. A method as claimed in claim 1, wherein a subscriber data network number is translated into the corresponding international mobile station identity.
3. A method as claimed in claim 1, wherein each subscriber terminal is allocated a roaming data number.
4. A mobile communications network having means for delivery of packet data services from a packet data network to mobile terminals served by the mobile network, the mobile network including a mobile switching centre for providing voice communication facilities to mobile terminals via respective base station controllers and base stations, a home location register for storing information relating to said mobile terminals, and packet switching means providing an interface between the packet data network and said mobile terminals via the respective base station controllers, the network including means for encapsulating each data packet, means for retrieving from the mobile network to the data packet network said stored

information indicative of the mobile network location of each said mobile terminal adapted to receive packet data services, means for providing each said encapsulated data packet with a temporary address corresponding to said mobile network location whereby that  
5 packet is routed via the packet switch to the base station controller serving that mobile terminal, and means for decapsulating the data packet, and delivering the packet to the mobile terminal.

5. A mobile communications network having means for  
10 delivery of packet data services from a packet data network to mobile terminals served by the mobile network, the mobile network including a mobile switching centre for providing voice communication facilities to mobile terminals via respective base station controllers and base  
15 stations, a home location register for storing information relating to said mobile terminals, a packet routing system comprising a gateway support node providing an interface with the packet data network and one or more serving support nodes each coupled to the gateway support node and to one or more base station controllers for delivery of data packets to the mobile terminals, the packet routing system  
20 including means for encapsulating each data packet, means for retrieving from the mobile network to the data packet network said stored information indicative of the mobile network location of each said mobile terminal adapted to receive packet data services, means for providing each said encapsulated data packet with a temporary  
25 address corresponding to said mobile network location whereby that packet is routed via the packet switch to the base station controller serving that mobile terminal, and means for decapsulating the data packet, and delivering the packet to the mobile terminal.

30 6. A mobile communications network as claimed in claim 5, wherein the packet network has means for encapsulating packet data in a first format for transport between the gateway support node and a said serving support node and in a second format for transport between a said serving support node and a said base station  
35 controller.

1/5






Fig. 2.

Fig. 5.




Fig. 6.



Fig.3a.




Fig.3b.








Fig.4.



5/5

Fig.4 (Cont).



## INTERNATIONAL SEARCH REPORT

International Application No  
PC1, GB 96/02962A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04Q7/22 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 95 28063 A (NOKIA TELECOMMUNICATIONS OY ET AL) 19 October 1995 see page 11, line 32 - page 18, line 2 ---	1,2,4,5
A	ISS '95. WORLD TELECOMMUNICATIONS CONGRESS. XV INTERNATIONAL SWITCHING SYMPOSIUM. 23 - 28 APRIL 1995. ADVANCED SWITCHING TECHNOLOGIES FOR UNIVERSAL TELECOMMUNICATIONS AT THE BEGINNING OF THE 21ST CENTURY. PROCEEDINGS VOL. 1, BERLIN, DE . pages 36-40, XP000495534 MADAMANN F: "GENERAL PACKET RADIO SERVICE - A PACKET MODE SERVICE WITHIN THE GSM" see the whole document -----	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \* "A" document defining the general state of the art which is not considered to be of particular relevance
- \* "E" earlier document but published on or after the international filing date
- \* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \* "O" document referring to an oral disclosure, use, exhibition or other means
- \* "P" document published prior to the international filing date but later than the priority date claimed

- \* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \* "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \* "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \* "Δ" document member of the same patent family

Date of the actual completion of the international search

13 March 1997

Date of mailing of the international search report

27.03.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Behringer, L.V.

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT, GB 96/02962

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9528063 A	19-10-95	FI 941652 A	09-10-95
		AU 2778795 A	30-10-95
		EP 0754395 A	22-01-97
-----			

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: \_\_\_\_\_**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**